

磨齿直齿轮·压力角 20°

模数 1·凸缘型

大批量
订购 
bulk order


■ 模数 1·凸缘型

进口
产品



按图定制 >

① 代号	类型	材质	热处理	齿面硬度
GKADKA	凸缘型	15CrMo	渗碳淬火	55~60HRC



订购编号示例

① 代号	-	② 模数	-	③ 齿数	-	④ 轴孔直径 dr
GKADKA	-	1	-	20	-	K10

▲ 精度等级 JIS B 1702-1 5 级。

① 代号	② 模数	③ 齿数	④ 轴孔直径 dr	G 分度圆 直径	D 齿顶圆 直径	d 齿根圆 直径	H	B	L	L ₁	许用扭矩 (N·m)		许用扭矩 (kgf·m)		侧隙(mm)	质量 (kg)						
											弯曲强度	齿面强度	弯曲强度	齿面强度								
GKADKA	1	18	8	18	20	15.5	15	10	15	5	12.1	6.37	1.24	0.65	0.08-0.16	0.02						
		20	8	K10	20	22	17.5										17	14.2	8.04	1.45	0.82	0.027
		24	K10	12	24	26	21.5										20	18.5	12	1.88	1.22	0.038
		25	K10	12	25	27	22.5										20	19.6	13.1	2	1.33	0.041
		30	K10	12	30	32	27.5										25	25.1	19	2.56	1.94	0.065
		35	K10	15	35	37	32.5										25	30.7	26.2	3.13	2.67	0.085
		36	12	15	36	38	33.5										25	31.9	27.8	3.25	2.84	0.085
		40	12	15	40	42	37.5										30	36.5	34.6	3.72	3.53	0.11
		45	12	15	45	47	42.5										30	42.3	44.3	4.31	4.51	0.14
		48	12	15	48	50	45.5										30	45.8	50.6	4.67	5.16	0.16
		50	12	15	50	52	47.5										35	48.1	55.1	4.91	5.62	0.18
		55	15	20	55	57	52.5										40	54	67.3	5.51	6.86	0.26
		60	15	20	60	62	57.5										40	59.9	80.6	6.11	8.22	0.29
		70	20	25	70	72	67.5										45	71.9	111	7.33	11.4	0.37
		80	20	25	80	82	77.5										45	83.9	147	8.55	15	0.47
		100	20	25	100	102	97.5										45	103	224	10.5	22.8	0.69

dr		b		t	
基准尺寸	公差	基准尺寸	公差	基准尺寸	公差
8	+0.015	3	±0.0125	1.4	+0.1 0
K10	0	4	±0.015	1.8	
12	+0.018	4		1.8	
15	0	5		2.3	
20	+0.021 0	6	±0.018	2.8	+0.2 0
25		8		3.3	

