



Gelenkköpfe Maßreihe E
Gleitpaarung: Stahl auf Stahl
wartungspflichtig

Innenring:
Wälzlagerstahl, gehärtet, geschliffen.

Außenring:
Wälzlagerstahl gehärtet, geschliffen. Zur Montage des Innenrings wird der Außenring gesprengt.

Gehäuse:
Stahlgehäuse, alle Größen verzinkt und chromatiert. Gelenklager wird ins Gehäuse gepresst und beidseitig verstemmt.

Schmiernippel:
Größe 6 bis 15 ohne Schmiernippel, ab Größe 17 mit Schmiernippel DIN 3405 Form D.

Wartungs- und Bedienungsanleitung unter www.askubal.de/service/bedienungs-und-wartungsanleitungen/



Rod ends dimension series E
Mating materials: Steel on steel
Maintenance required

Inner ring:
Antifriction bearing steel, hardened, ground.

Outer ring:
Antifriction bearing steel, hardened, ground.
Outer ring is split for assembly of inner ring.

Housing:
Made of steel, all sizes galvanized and chromated. The spherical bearing is pressed into the housing and caulked at both sides.

Lubrication nipple:
Sizes 6 to 15 without lubricating nipple, sizes 17 to 30 nipple DIN 3405 shape D.

Instruction and maintenance manual see www.askubal.de/en/service/instruction-and-maintenance-manual/