

法兰一体型无油衬套 铜合金嵌入式法兰型·中间法兰型 / 无油铜合金垫片

code 5天发货


直线运动部品

选型指南

标准	举例	型号	-	L	型号
	Code	D			Code No.
	CT27T	8	-	25	OBW 8


- ◆材质 高强度黄铜合金类镶嵌固体润滑剂
- ◆附件 短头内六角螺栓2~4个

■ 嵌入式法兰型




● 圆法兰型

CT27T (嵌入式法兰型)
CT29T (中间法兰型)






● 侧切法兰型

CT28T (嵌入式法兰型)
CT30T (中间法兰型)



■ 中间法兰型





注: 推荐配套轴: d8:一般用(重载) e7:一般用(轻载) f8:高精度用 g6:高精度用(间歇运转)使用
注: 推荐用止转螺丝固定衬套。

型号		L	D _{n7}	D _a	L ₁	Ha	T	t	d ₁	d ₂	P. C. D.	F	A	附件 短头内六角螺栓
Code	d _{F7}													
嵌入式法兰型	8	20 (25)	12	11.5	5	27	4	2.3	3.5	6	19	19	19	M3-10×2
	10	25 30	14	13.5	29	29	5	3	4	7	21	21	21	
	12	25 30	18	17.5	36	6	37	5	3.1	4.5	7.5	26	26	M4-12×2
中间法兰型	13	(25) (30) 35	19	18.5	37	5	3	1	4.5	7.5	27	27	27	M4-12×2
	16	25 30 35 40	22	21.5	40	8	4	3.8	5.5	9	30	18	24	M4-12×4
	20	30 35 40 50	28	27.5	49	6	3	8	5.5	9	38	22	31	M5-16×4
带()的L尺寸 仅限于嵌入式 法兰型	25	(30) (35) (40) (50) 60	33	32.5	54	8	4	4.3	6.6	11	43	25	35	M6-20×4
	30	(35) (40) (50) (60) 70	38	37.5	63	10	4	4.3	6.6	11	50	30	40	M6-20×4
	35	(50) 70	44	43.5	69	10	4	4.3	6.6	11	56	36	43	M6-20×4
带()的L尺寸 仅限于嵌入式 法兰型	40	(60) (70) 80	50	49.5	82	10	5	5.3	9	14	66	38	54	M8-25×4
	50	(70) 100	62	61.5	94	13	5	5.3	9	14	78	50	60	M8-25×4

■ 无油铜合金垫片(平头螺栓型)

◆材质: 高强度黄铜合金类镶嵌固体润滑剂



型号		T	容差	D	容差	D _a	安装孔			倒角	
Code	No.						P. C. D.	数量	OBW 平头螺栓	a	b
OBW	10	3	0 -0.1	10.2	+0.2 +0.1	30	20	2	M3	2	0.4
	12			12.2		40	28				
	13			13.2							
	15			15.2							
	16			16.2							
	18	18.2									
	20	20.2	5	0	25.2	50	35	2	M5	2.5	0.4
	25	25.2			55	40					
	30	30.2			60	45					
	35	35.2			70	50					
40	40.2	80			60						
50	50.3	8	0	50.3	100	75	4	M6	3 4	0.5 0.6	

单轴
机械手

直线模组

单轴组件

手动组件

防尘罩

导向轴

导向轴
支座

固定环

直线轴承

直线轴承
组件

微型
滚珠衬套

无油衬套
及组件

直线导轨

导轨配件

滚珠丝杠

丝杠支座

梯形丝杠
及支座

位置
显示器

抽屜导轨

线性滑轨

花键