



带法兰滚珠轴承 (小径·深沟) 双盖式

5天发货

选型指南

标准	型号 Code
举例	BF6803ZZ



Code		材质
国产	进口	
C-BF6□□ZZ	BF6□□ZZ	SUJ2
C-BF6□□AZZ	BF6□□AZZ	
C-BF6□□ZZ	BF6□□ZZ	
C-BFM1□□AZZ	BFM1□□AZZ	

◆轴承精度: GB 307 P0
JIS B 1514 0级

分度盘

行星减速机

联轴器·万向节

免键衬套

轴承

凸轮·滚子轴承

轴承座组件

齿轮齿条·磁力轮

转轴

悬臂销

铰链销

支点用台阶螺丝

型号		d	D	B	D ₁	C	r (min)	基本额定负载		容许转速 rpm (参考)	安装尺寸		重量 (g) (参考)				
国产	进口							Cr(动)N	Cor(静)N		D _s (min)	R (max)					
C-BF682ZZ	BF682ZZ	2	5	2.3	6.1	0.6	0.08	169	50	85000	2.7	0.08	0.22				
C-BF692ZZ	BF692ZZ							3	7.5		0.8	330		98	75000	3	0.15
C-BF682AZZ	BF682AZZ			6	2.6	7.1	2.5	0.15	208		74	71000		3.7	0.08	0.36	
C-BF692AZZ	BF692AZZ	7	3.5	8.5	0.9	385			127	63000	3.85	0.15	0.68				
C-BF673ZZ	BF673ZZ	6	2.5	7.2	0.6	0.1			208	74	71000	3.6	0.08	0.33			
C-BF683ZZ	BF683ZZ	3	7	3	8.1	0.8	0.15	390	130	63000	3.9	0.1	0.53				
C-BF693ZZ	BF693ZZ							8	4		9.5	0.9		560	179	60000	4.2
C-BF603ZZ	BF603ZZ			9	5	10.5	1	570	187		56000	5.6		0.2	2.53		
C-BF623ZZ	BF623ZZ	10	4	11.5	4	0.1	630	218	50000	5	0.1		1.14				
C-BF674ZZ	BF674ZZ	7	2.5	8.2			0.6	0.1	222	88	60000	4.6	0.08	0.35			
C-BF684ZZ	BF684ZZ	9	10.3	1			0.15	640	224	53000	5.2	0.15	1.96				
C-BF694ZZ	BF694ZZ	4	11	4	12.5	1	0.2	957	345	48000	5.6	0.2	3.53				
C-BF604ZZ	BF604ZZ							12	13.5					1300	485	40000	0.08
C-BF624ZZ	BF624ZZ			13	5	15	0.15	715	281		45000	6.2		0.15	2.18		
C-BF675ZZ	BF675ZZ	5	8	2.5	9.2	0.6	0.1	217	91	53000	6.6	0.1	0.77				
C-BF685ZZ	BF685ZZ							11	5					12.5	0.15	715	281
C-BF695ZZ	BF695ZZ			13	4	15	1	1080	430					43000	7.6	0.2	4.26
C-BF605ZZ	BF605ZZ	6	10	3	11.2	0.6	0.1	465	196	45000	7	0.15	3.04				
C-BF686ZZ	BF686ZZ							13	15					1.1	0.15	1080	440
C-BF696ZZ	BF696ZZ			15	5	17	1.2	1350	530		38000	8		0.3	9.09		
C-BF606ZZ	BF606ZZ	7	17	6	19	1.5	0.3	2190	835	32000	8.8	0.1	1.15				
C-BF626ZZ	BF626ZZ							19	22					1.5	0.2	2336	885
C-BF678ZZ	BF678ZZ			12	3.5	13.6	0.8	0.1	515					252	40000	10	0.3
C-BF688ZZ	BF688ZZ	8	16	5	18	1.1	0.2	1610	710	36000	10	0.3	13				
C-BF698ZZ	BF698ZZ							19	6					22	1.5	1990	865
C-BF608ZZ	BF608ZZ			22	7	25	0.15	3350	1400		34000	12		0.3	6.1		
C-BF670ZZ	BF670ZZ	10	15	4	16.5	0.8	0.15	855	435	15000	10.3	0.15	2.1				
C-BF680ZZ	BF680ZZ							19	5					21	1	1716	840
C-BF690ZZ	BF690ZZ			22	6	25	1.5	2695	1273					34000	12.4	0.2	3.4
C-BF6701ZZ	BF6701ZZ	12	18	4	19.5	0.8	0.2	926	530	13000	14	0.3	7.2				
C-BF6801ZZ	BF6801ZZ							21	5					23	1.1	1915	1041
C-BF6901ZZ	BF6901ZZ			24	6	26.5	1.5	2886	1466					31000	17	0.3	19.9
C-BF6702ZZ	BF6702ZZ	15	21	4	22.5	0.8	0.2	937	582	11000	17.4	0.2	4.4				
C-BF6802ZZ	BF6802ZZ							24	5					26	1.1	2073	1253
C-BF6902ZZ	BF6902ZZ			28	7	30.5	1.5	4321	2259					26000	19	0.3	21.4
C-BF6703ZZ	BF6703ZZ	17	23	4	24.5	0.8	0.2	1000	658	9500	20.4	0.2	6.3				
C-BF6803ZZ	BF6803ZZ							26	5					28	1.1	2233	1456
C-BF6903ZZ	BF6903ZZ			30	7	32.5	1.5	4588	2565					23000	27	0.3	26.1
C-BF6704ZZ	BF6704ZZ	20	27	4	28.5	0.8	0.2	1041	729	8500	27	0.2	50.2				
C-BF6804ZZ	BF6804ZZ							32	7					35	1.5	4015	2462
C-BF6904ZZ	BF6904ZZ			37	9	40	2	6381	3682					19000	22	0.3	42.8
C-BF6805ZZ	BF6805ZZ	25	42	7	40	1.5	0.3	4303	2932	18000	27	0.2	26.1				
C-BF6905ZZ	BF6905ZZ							45	2					7001	4540	16000	27

■标准尺寸

型号		d	D	B	D ₁	C	r (min)	基本额定负载		容许转速 rpm (参考)	安装尺寸		重量 (g) (参考)			
国产	进口							Cr(动)N	Cor(静)N		D _s (min)	R (max)				
C-BFM104ZZ	BFM104ZZ	4	10	4	11.6	0.8	0.15	710	270	48000	5.9	0.15	1.5			
C-BFM105ZZ	BFM105ZZ	5						430	168		50000		6	1.38		
C-BFM126ZZ	BFM126ZZ	6						12	13.6		715		292	43000	7.2	1.86
C-BFM148ZZ	BFM148ZZ	8						14	15.6		817		385	38000	9.26	2.42