

5天发货


杆端关节轴承 内螺纹标准型

选型指南

标准	举例	型号
		Code d
		PH11C 5



Code	产地	类型		杆端		衬垫	内圈	
		螺纹类型	螺纹方向	材质	表面处理	材质	材质	热处理
PH11C	国产	内螺纹	右旋	碳钢	镀锌	铜	碳钢	淬火
PH11CL			左旋					



型号		B	dk	C1 (max)	d2 (max)	G (6H)	h1	L3 (min)	L4 (max)	L5	W	d4	d5	R1 (min)	a° ≈	额定负荷(KN)		重量 (kg)	
Code	d															动负荷	静负荷		
PH11C 右螺纹旋 PH11CL 左螺纹旋	5	8	11.11	6	18	M5×0.8	27	10	36	4	9	8.5	11	0.3	13	4.6	4.8	0.016	
	6	9	12.7	6.75	20	M6×1.0	30	12	40	5	11	10	13			6.1	6.5	0.022	
	8	12	15.88	9	24	M8×1.25	36	16	48	14	12.5	16	16			8.5	9.5	0.047	
	10	14	19.05	10.5	28	M10×1.5	43	20	57	6.5	17	15	19	0.6	13	9.7	12	0.077	
	10A					M10×1.25													
	12	16	22.23	12	32	M12×1.75	50	22	66	19	17.5	22	22			10.6	15	0.1	
	12A					M12×1.25													
	14	19	25.4	13.5	36	M14×2.0	57	25	75	8	22	20	25			16	17	22	0.16
	14A					M14×1.5													
	16	21	28.58	15	42	M16×2.0	64	28	85	10	27	25	31			15	19.7	27	0.22
	16A					M16×1.5													
	18	23	31.75	16.5	44	M18×1.5	71	32	93	10	27	25	31			14	29.8	40	0.42
	20	25	34.3	18	50	M20×1.5	77	33	102	12	32	30	38			15	40.2	48	0.488
	22	28	38.1	20	54	M22×1.5	84	37	111	12	36	33.5	42	15	44	55	0.54		
	25	31	42.86	22	60	M24×2.0	94	42	124	14	37	46	46		52.2	65	0.72		
	28	35	47.63	24	66	M27×2.0	103	51	136	14	41	40	50		17	60.2	78	1.1	
	30	37	50.8	25	70	M30×2.0	110	145	15	41	40	50	58	16	17	-	-	2.4	
	30A					M27×2.0													
	35	43	57.1	28	81	M36×2.0	125	56	165.5	17	50	46	58	12	1.6				
	40	49	66.6	33	91	M42×2.0	142	60	187.5	19	55	53	65	1	17	-	-	2.4	
50	60	82.5	45	117	M48×2.0	160	65	218.5	23	65	65	75	1	12	-	-	5		

分度盘

行星  
减速机

联轴器·  
万向节

免键衬套

轴承

凸轮·  
滚子轴承

轴承座  
组件

齿轮齿条·  
磁力轮

转轴

悬臂销

铰链销

支点用  
台阶螺丝