

平键 标准型/长度指定型

小零件

选型指南

举例	型号	
Code	B	L
标准	KKEB	10 - 30




标准型



KKEA
KKEAS (不锈钢)

KKEB
KKEBS (不锈钢)

KKEG
KKEGS (不锈钢)



Code	材质	抗拉强度
KKEA KKEB KKEC	S45C	600N/mm ² 以上
KKEAS KKEBS KKECS	SUS316	600N/mm ² 以上

L	公差
最短~10	0 -0.36
11~18	0 -0.43
19~30	0 -0.52
31~50	0 -0.62
51~80	0 -0.74
81~110	0 -0.87

圆线弹簧

拉簧

扭簧 碟簧
氮气弹簧

矩形弹簧

扣环

平键

销子

磁铁

小零件

密封圈

垫圈

轴环

精密垫片

螺丝

螺母
垫圈

型号		L										Ha 公差		C							
Code	B	公差																			
KKEA KKEB KKEC	2	0	6	8	10	15	20						2	0	0.16 ~ 0.25						
	3	-0.025	6	8	10	12	15	16	18	20	25	30	3	-0.025							
	4	0	8	10	12	15	16	18	20	25	30	35	40	45		50	4	0			
	5	-0.03	10 12 15 16 18 20 22 25 28 30 32 35 40 45 50 55 60										5	-0.03	0.25 ~ 0.4						
	6	0	10 12 15 16 18 20 22 25 28 30 32 35 40 45 50 55 60										6	0							
	KKEAS KKEBS KKECS	7	-0.036	15		20	22	25	28	30	32	35	40	45	50	60	70	7	0 -0.036	0.4 ~ 0.6	
8		0	10 12 15 16 18 20 22 25 28 30 32 35 40 45 50 55 60 65 70 80 90										7	0							
10		-0.043	15		16	18	20	25	30	35	40	45	50	55	60	65	70	80	90		8
12		0	20		25	30	35	40	45	50	55	60	65	70	80	90	8	0			
14		-0.043	30		35	40	45	50	55	60	65	70	80	90	9	-0.09					
15		0	30		35	40	45	50	55	60	70	80	90	10	0						
16	-0.043	40				45	50	55	60	70	80	90	100	10	0						
18	0	40				45	50	55	60	70	80	90	100	110	11	0 -0.110					

长度指定型



KKEAL

KKEBL

KKECL



Code	材质	抗拉强度
KKEAL · KKEBL · KKECL	S45C	600N/mm ² 以上

型号		L		Ha 公差		C
Code	Bh9	最小单位1mm				
KKEAL KKEBL KKECL	2	0	5~50	3	0	0.16~0.25
	3	-0.025	6~60	4	-0.025	
	4	0	6~70	5	0	
	5	-0.03	8~70	6	-0.03	0.25~0.40
	6	0	8~80	7	0	
	8	-0.036	10~100	8	0	0.40~0.60
	10	0	15~100	9	-0.09	
	12	-0.043	15~150	10	0	
	14	0	15~150	11	0	
15	-0.043	18~150				
16	0	20~150				
18	-0.043	30~150				

L	公差
最短~10	0 -0.36
11~18	0 -0.43
19~30	0 -0.52
31~50	0 -0.62
51~80	0 -0.74
81~150	0 -0.87