

# 482.6 mm (19") installation system

## 482.6 mm (19") installation

### Assembly screws

#### M5 x 16 mm/M6 x 16 mm

For electronic equipment, 482.6 mm (19") installed components and blanking plates.

#### Supply includes:

- Plastic washers

Version	Packs of	Model No.
Phillips-head screw M5	50 pc(s).	<b>7094.120</b>
Cheese-head screw M6	50 pc(s).	<b>7094.110</b>
Phillips-head screw M6	50 pc(s).	<b>7094.100</b>



### Front-mounting cage nut, 482.6 mm (19")

The front-mounting cage nut consists of an expanding cage which is simply inserted into the square attachment hole at the front and then secured with the assembly screw.

When tightening the screw, the cage expands and thus secures the required components.

Clamping range from 1.2 – 4.5 mm.

Multi-tooth screw head, bit size T 30.

#### Material:

- Sheet steel


#### Surface finish:

- Zinc-plated

#### Supply includes:

- 50 expanding nuts
- Assembly screws
- Plastic washers

Size mm	Mounting hole size mm	Packs of	Model No.
M6 x 16	9.5 x 9.5	50 pc(s).	<b>2094.400</b>



### Spring nuts with screws

#### M6 x 10 mm for T-slot mounting angle

The spring nuts ensure flexible, secure mounting of accessory components on T-slot mounting angles.

#### Supply includes:

- 50 spring nuts
- 50 screws, 10 mm, self-locking

Version	Packs of	Model No.
Phillips-head, M6	50 pc(s).	<b>7000.990</b>

